

## SIP Office Ringer

The CyberData SIP-enabled SIP Office Ringer is a Power-over-Ethernet (PoE 802.3af) and Voice-over-IP (VoIP) notification device that easily connects into existing local area networks (LANs) with a single cable connection. The SIP Office Ringer provides a user uploadable audible ring indication when part of a ring group. The SIP Office Ringer also supports direct SIP voice paging and priority-based Multicast broadcasts.

### Typical Applications

- Office Environment Ringer
- General Paging
- Mass Notification

### Features

- Faster Processor
- Supports Cisco SRST
- User uploadable ring/messages
- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Network web management
- Network adjustable speaker volume
- Network downloadable firmware
- Concurrent SIP and multicast paging
- Dry relay contact for auxiliary control (controls external power)
- Peer-to-peer capable
- Sensor and tamper alert signal



### Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply
Speaker Output	1 Watt Peak Power
On-Board Relay	1A at 30 VDC
Operating Temperature	-10° C to 50° C (14° F to 122° F)
Payload Types	G711, A-law and $\mu$ -law
Dimensions	4.53 inches [115 mm] Length 2.14 inches [54.3 mm] Width 4.53 inches [115 mm] Height
Warranty	2 years limited
Weight	1.0 lbs. (0.45 kg)
Boxed Weight	2.0 lbs. (0.90 kg)
Part Number	011216, RAL 9003, Signal White

The following products are also available:



Indoor Intercom  
#011211



Emergency Intercom  
#011209



Outdoor Intercom  
#011186



Outdoor Keypad Intercom  
#011214

# SIP Office Ringer

